


Technical data sheet



Description	Name	321 Slide Concept Single		
	Line	Personal		
	Descriptions	1-part sliding door		
	Mounting possibilities	Can be mounted between 2 walls		
Measurements	Article	Width	Height	Left/Right
	321 001 001S ###	up to 1000 mm	up to 2044 mm	Left
	321 002 001S ###	1001 mm-1200 mm	up to 2044 mm	Left
	321 003 001S ###	1201 mm-1400 mm	up to 2044 mm	Left
	321 004 001S ###	1401 mm-1600 mm	up to 2044 mm	Left
	321 005 001S ###	1601 mm-1800 mm	up to 2044 mm	Left
	321 006 001S ###	1801 mm-2000 mm	up to 2044 mm	Left
	321 001 002S ###	up to 1000 mm	up to 2044 mm	Left
	321 002 002S ###	1001 mm-1200 mm	up to 2044 mm	Right
	321 003 002S ###	1201 mm-1400 mm	up to 2044 mm	Right
	321 004 002S ###	1401 mm-1600 mm	up to 2044 mm	Right
	321 005 002S ###	1601 mm-1800 mm	up to 2044 mm	Right
	321 006 002S ###	1801 mm-2000 mm	up to 2044 mm	Right
Made to measure	Made to measure per mm, max. width 2000mm. Extra height with additional costs			
General!!!	Door section max. 800mm at height 2044mm			
Glass beveling	Included			
Glass	Glass specifications	8 mm toughened safety glass (norm NBN 23-002, klasse NBN EN 12600)		
	Type of glass	101 Transparent	107 Green	119 Opal white
		130 Timeless	108 Blue	120 Opal Black
	102 Opal mat	114 Crepi	125 Opal bronze	
	104 Extra transparent	115 Cathedral	126 Opal gris	
	105 Bronze	118 Black	121 Mirror	
	106 Gris			
Glass treatments	109 Aquaclean	110 Zone intime	111 Zone à la carte	
	112 Print			
Finishing	Characteristics	Profile above glass square knob Softclose system Folding floor guide for easy cleaning		
	Finishing ###	Shiny (011), Matte (001), Black matte (099), white matte (088)		
Service	Checking of measurements	Included in the price		
	Mounting	Possible at an additional cost		
	Mounting guidelines	Available		
Seats	Characteristics	UV-resistant according to Xenon test 1200 with cycle 120/18		
		Crystal-clear color according to RAU-PVC1107 Mold resistance according to DIN 5373		
Technical details	Advice	A profile or glass must always be placed on the tiling. Otherwise, this can lead to issues with waterproofing.		
		When preparing, take into account the size and weight of the glass. Can the glass be brought into and installed in the bathroom.		

