

Technical data sheet



Description	Name	322 Slide Concept		
	Line	Personal		
	Descriptions	4-part sliding door with 2 fixed panel		
	Mounting possibilities	Can be mounted between 2 walls Can be combined with 330/ 2x330		
Measurements	Article	Width	Height	Left/Right
	322 001 000 ###	up to 1200 mm	up to 2044 mm	
	322 002 000 ###	1201 mm-1400 mm	up to 2044 mm	
	322 003 000 ###	1401 mm-1600 mm	up to 2044 mm	
	322 004 000 ###	1601 mm-1800 mm	up to 2044 mm	
	322 005 000 ###	1801 mm-2000 mm	up to 2044 mm	
	322 008 000 ###	2001 mm-2500 mm	up to 2044 mm	
	322 009 000 ###	2501 mm-3000 mm	up to 2044 mm	
	Made to measure	Made to measure per mm, max. width 3000 mm. Extra height with additional costs		
	Glass beveling	Included		
Glass	Glass specifications	8 mm toughened safety glass (norm NBN 23-002, klasse NBN EN 12600)		
	Type of glass	101 Transparent	107 Green	119 Opal white
		130 Timeless	108 Blue	120 Opal Black
		102 Opal mat	114 Crepi	125 Opal bronze
		104 Extra transparent	115 Cathedral	126 Opal gris
		105 Bronze	118 Black	121 Mirror
		106 Gris		
	Glass treatments	109 Aquaclean	110 Zone intime	111 Zone à la carte
		112 Print		
Finishing	Characteristics	Profile above glass square knob Softclose system Folding floor guide for easy cleaning		
	Finishing ###	Shiny (011), Matte (001), Black matte (099), white matte (088)		
Service	Checking of measurements	Included in the price		
	Mounting	Possible at an additional cost		
	Mounting guidelines	Available		
Seals	Characteristics	UV-resistant according to Xenon test 1200 with cycle 120/18		
		Crystal-clear color according to RAU-PVC1107 Mold resistance according to DIN 5373		
Technical details	Advice	A profile or glass must always be placed on the tiling. Otherwise, this can lead to issues with waterproofing.		
		When preparing, take into account the size and weight of the glass. Can the glass be brought into and installed in the bathroom.		

