

Technical data sheet



Description	Name	325 Slide Concept		
	Line	Personal		
	Descriptions	3-part sliding door with 2 fixed panels		
	Mounting possibilities	Can be mounted between 2 walls Can be combined with 330 / 2x330		
Measurements	Article	Width	Height	Left/Right
	325 001 001 ###	up to 1200 mm	up to 2044 mm	Left
	325 002 001 ###	1201 mm-1400 mm	up to 2044 mm	Left
	325 003 001 ###	1401 mm-1600 mm	up to 2044 mm	Left
	325 004 001 ###	1601 mm-1800 mm	up to 2044 mm	Left
	325 005 001 ###	1801 mm-2000 mm	up to 2044 mm	Left
	325 008 001 ###	2001 mm - 2500 mm	up to 2044 mm	Left
	325 009 001 ###	2501 mm - 3000 mm	up to 2044 mm	Left
	325 001 002 ###	up to 1200 mm	up to 2044 mm	Right
	325 002 002 ###	1201 mm-1400 mm	up to 2044 mm	Right
	325 003 002 ###	1401 mm-1600 mm	up to 2044 mm	Right
	325 004 002 ###	1601 mm-1800 mm	up to 2044 mm	Right
	325 005 002 ###	1801 mm-2000 mm	up to 2044 mm	Right
	325 008 002 ###	2001 mm - 2500 mm	up to 2044 mm	Right
	325 009 002 ###	2501 mm - 3000 mm	up to 2044 mm	Right
	Made to measure	Made to measure per mm, max. width 2000mm. Extra height with additional costs		
	General!!!	Door section max. 800mm at height 2044mm		
	Glass beveling	Included		
Glass	Glass specifications	8 mm toughened safety glass (norm NBN 23-002, klasse NBN EN 12600)		
	Type of glass	101 Transparent	107 Green	119 Opal white
		130 Timeless	108 Blue	120 Opal Black
		102 Opal mat	114 Crepi	125 Opal bronze
		104 Extra transparent	115 Cathedral	126 Opal gris
		105 Bronze	118 Black	121 Mirror
		106 Gris		
	Glass treatments	109 Aquaclean	110 Zone intime	111 Zone à la carte
		112 Print		
Finishing	Characteristics	Profile above glass square knob Softclose system Folding floor guide for easy cleaning		
	Finishing ###	Shiny (011), Matte (001), Black matte (099), white matte (088)		
Service	Checking of measurements	Included in the price		
	Mounting	Possible at an additional cost		
	Mounting guidelines	Available		
Seals	Characteristics	UV-resistant according to Xenon test 1200 with cycle 120/18		
		Crystal-clear color according to RAU-PVC1107 Mold resistance according to DIN 5373		
Technical details	Advice	A profile or glass must always be placed on the tiling. Otherwise, this can lead to issues with waterproofing.		
		When preparing, take into account the size and weight of the glass. Can the glass be brought into and installed in the bathroom.		

